

TEI BY EXAMPLE

`<TBE:eg>`
TEI
By
Example
`</TBE:eg>`

MODULE 0: INTRODUCTION TO TEXT ENCODING AND THE TEI

Ron Van den Branden

Edward Vanhoutte

Melissa Terras

Centre for Scholarly Editing and Document Studies (CTB), Royal
Academy of Dutch Language and Literature, Belgium, Gent, 9 July 2010

Last updated September 2020

Licensed under a Creative Commons Attribution ShareAlike 3.0 License

TABLE OF CONTENTS

2. LaTeX.....	1
---------------	---

2. LaTeX

This example illustrates how the text above could be encoded in LaTeX, an open source typesetting language that can be interpreted by TeX typesetting programs for producing fixed-layout representations such as PDF. LaTeX is not an XML format, and makes use of “procedural” markup, whose meta-information (starting with the `\` character) are instructions for the rendering software on the layout of the text content. As you can see, the actual text contents are preceded by a declaration of several style aspects determining how the text has to be rendered on a page. The text is divided captured as a `{document}`, in which all italicised words are indicated as italicised (`\textit{}`), without difference between the reasons for this typographic emphasis. The footnote is distinguished (`\footnote{}`), but there is no way of telling the computer that “Goethe” is a proper name.

```
\documentclass[12pt]{article}
\usepackage{makeidx}
\usepackage{multirow}
\usepackage{multicol}
\usepackage[dvipsnames,svgnames,table]{xcolor}
\usepackage[dvips]{graphicx}
\usepackage{ulem}
\usepackage{hyperref}
\author{the TBE crew}
\title{Statement}
\setlength{\paperwidth}{419pt}
\setlength{\paperheight}{595pt}
\setlength{\textheight}{451pt}
\setlength{\textwidth}{239pt}
\setlength{\voffset}{-72pt}
\setlength{\hoffset}{-72pt}
\setlength{\evensidemargin}{90pt}
\setlength{\oddsidemargin}{90pt}
\setlength{\topmargin}{39pt}
\setlength{\headheight}{13pt}
\setlength{\headsep}{20pt}
\makeatletter
\newenvironment{indentation}[3]%
{\par\setlength{\parindent}{#3}
\setlength{\leftmargin}{#1} \setlength{\rightmargin}{#2}%
```

```
\advance\linewidth -\leftmargin      \advance\linewidth -\rightmargin%
\advance\@totalleftmargin\leftmargin  \setpar{\@@par}}%
\parshape 1\@totalleftmargin \linewidth\ignorespaces}{\par}%
\makeatother
% new LaTeX commands
\newcommand{\styleCaption}[1]{\textit{#1}}
\newcommand{\styleEndnoteCharacters}[1]{#1}
\newcommand{\styleFootnoteCharacters}[1]{${}^{#1}$}
\newcommand{\styleHeading}[1]{\large \textsf{#1}}
\newcommand{\styleIndex}[1]{#1}
\newcommand{\styleStandaardlinealettertypeOne}[1]{#1}
\begin{document}
\section{\textsf{Review}}
{\raggedright
\begin{indentation}{0pt}{0pt}{0pt}
{\large \textit{Die Leiden des jungen Werther}\footnote{ by Goethe
}} is an \textit{exceptionally} good example of a book full of
\textit{Weltschmerz}.)}
\end{indentation}
}
\end{document}
```

Example 1. A LaTeX example.