

# TEI BY EXAMPLE

0101010101010101  
<TBE:eg>  
TEI  
By  
Example  
</TBE:eg>  
1010101010101010  
0101010101010101  
1010101010101010

## MODULE 0: INTRODUCTION TO TEXT ENCODING AND THE TEI

Ron Van den Branden

Edward Vanhoutte

Melissa Terras

---

Centre for Scholarly Editing and Document Studies (CTB), Royal  
Academy of Dutch Language and Literature, Belgium, Gent, 9 July 2010

Last updated September 2020

Licensed under a Creative Commons Attribution ShareAlike 3.0 License



## TABLE OF CONTENTS

3. OpenDocument Format.....	1
-----------------------------	---



### 3. OpenDocument Format

The same document can be encoded in the OpenDocument Format, an XML encoding scheme for representing electronic documents such as spreadsheets, charts, presentations and word processing documents, that can be interpreted by (desktop) publishing systems such as the Open Office software suite. Notice that, despite ODF being expressed in XML, there are many similarities to the LaTeX approach in the previous example. ODF is a procedural encoding scheme as well, providing an XML vocabulary to describe different *formatting styles*. The text itself is encoded in a `<office:text>` element, in which several structural elements are distinguished: headings, paragraphs, footnotes, each with their own associated rendering instructions in the form of styles. All italicised text is represented in the encoding, with references to different style definitions that are responsible for rendering the text italic in the output. Here, too, there is no way of indicating that the visually unmarked “Goethe” is a proper name.

```
<office:document-content xmlns:oooc="http://openoffice.org/2004/calc"
  xmlns:dom="http://www.w3.org/2001/xml-events" xmlns:xsd="http://www.w3.org/2001/
XMLSchema" xmlns:fo="urn:oasis:names:tc:opendocument:xmlns:xsl-fo-compatible:1.0"
  xmlns:ooo="http://openoffice.org/2004/office" xmlns:xsi="http://www.w3.org/2001/
XMLSchema-instance" xmlns:number="urn:oasis:names:tc:opendocument:xmlns:datastyle:1.0"
  xmlns:of="urn:oasis:names:tc:opendocument:xmlns:of:1.2"
  xmlns:rdfa="http://docs.oasis-open.org/opendocument/meta/rdfa#"
  xmlns:text="urn:oasis:names:tc:opendocument:xmlns:text:1.0"
  xmlns:table="urn:oasis:names:tc:opendocument:xmlns:table:1.0" xmlns:xforms="http://
www.w3.org/2002/xforms" xmlns:svg="urn:oasis:names:tc:opendocument:xmlns:svg-
compatible:1.0" xmlns:draw="urn:oasis:names:tc:opendocument:xmlns:drawing:1.0"
  xmlns:script="urn:oasis:names:tc:opendocument:xmlns:script:1.0"
  xmlns:dr3d="urn:oasis:names:tc:opendocument:xmlns:dr3d:1.0"
  xmlns:form="urn:oasis:names:tc:opendocument:xmlns:form:1.0"
  xmlns:field="urn:openoffice:names:experimental:ooo-ms-interop:xmlns:field:1.0"
  xmlns:meta="urn:oasis:names:tc:opendocument:xmlns:meta:1.0"
  xmlns:rpt="http://openoffice.org/2005/report"
  xmlns:style="urn:oasis:names:tc:opendocument:xmlns:style:1.0" xmlns:math="http://
www.w3.org/1998/Math/MathML" xmlns:ooow="http://openoffice.org/2004/
writer" xmlns:chart="urn:oasis:names:tc:opendocument:xmlns:chart:1.0"
  xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:dc="http://purl.org/dc/elements/1.1/"
  xmlns:office="urn:oasis:names:tc:opendocument:xmlns:office:1.0" office:version="1.2">
```

```
</office:scripts/>
<office:font-face-decls>
  <style:font-face style:name="Tahoma1" svg:font-family="Tahoma"/>
  <style:font-face style:name="Times New Roman" svg:font-family="'Times New
    Roman'" style:font-family-generic="roman" style:font-pitch="variable"/>
  <style:font-face style:name="Arial" svg:font-family="Arial" style:font-family-
    generic="swiss" style:font-pitch="variable"/>
  <style:font-face style:name="Lucida Sans Unicode" svg:font-family="'Lucida Sans
    Unicode'" style:font-family-generic="system" style:font-pitch="variable"/>
  <style:font-face style:name="Tahoma" svg:font-family="Tahoma" style:font-family-
    generic="system" style:font-pitch="variable"/>
</office:font-face-decls>
<office:automatic-styles>
  <style:style style:name="P1" style:family="paragraph" style:parent-style-
    name="Heading_20_1" style:master-page-name="Standard">
    <style:paragraph-properties style:page-number="auto"/>
  </style:style>
  <style:style style:name="P2" style:family="paragraph" style:parent-style-
    name="Standard">
    <style:paragraph-properties fo:line-height="150%"/>
  </style:style>
  <style:style style:name="T1" style:family="text">
    <style:text-properties fo:language="nl" fo:country="BE"/>
  </style:style>
  <style:style style:name="T2" style:family="text">
    <style:text-properties fo:font-style="italic" style:font-style-asian="italic"/>
  </style:style>
  <style:style style:name="T3" style:family="text">
    <style:text-properties fo:font-size="14pt" style:font-size-
      asian="14pt" style:font-size-complex="14pt"/>
  </style:style>
  <style:style style:name="T4" style:family="text">
    <style:text-properties fo:font-size="14pt" fo:font-style="italic" style:font-size-
      asian="14pt" style:font-style-asian="italic" style:font-size-complex="14pt"/>
  </style:style>
  <style:style style:name="T5" style:family="text">
```

```

<style:text-properties fo:font-
size="12pt" fo:language="nl" fo:country="BE" style:font-size-
asian="12pt" style:font-size-complex="12pt"/>
</style:style>
</office:automatic-styles>
<office:body>
<office:text>
<office:forms form:automatic-focus="false" form:apply-design-mode="false"/>
<text:sequence-decls>
<text:sequence-decl text:display-outline-level="0" text:name="Illustration"/>
<text:sequence-decl text:display-outline-level="0" text:name="Table"/>
<text:sequence-decl text:display-outline-level="0" text:name="Text"/>
<text:sequence-decl text:display-outline-level="0" text:name="Drawing"/>
</text:sequence-decls>
<text:h text:style-name="P1" text:outline-level="1">Review</text:h>
<text:p text:style-name="P2">
<text:span text:style-name="T4">Die Leiden des jungen Werther</text:span>
<text:span text:style-name="Footnote_20_Symbol">
<text:span text:style-name="T4">
<text:note text:id="ftn1" text:note-class="footnote">
<text:note-citation>1</text:note-citation>
<text:note-body>
<text:p text:style-name="Footnote">
<text:s/>
<text:span text:style-name="T5">by Goethe</text:span>
</text:p>
</text:note-body>
</text:note>
</text:span>
</text:span>
<text:span text:style-name="T3"> is an </text:span>
<text:span text:style-name="T4">exceptionally</text:span>
<text:span text:style-name="T3"> good example of a book full of </text:span>
<text:span text:style-name="T4">Weltschmerz</text:span>
<text:span text:style-name="T3">.</text:span>
</text:p>
</office:text>
</office:body>

```

```
</office:document-content>
```

**Example 2. An OpenDocument example.**